

*Enviro EF3 Pellet Stoves and Inserts*



Medium Sized  
Pellet Stoves and  
Fireplace Inserts



# Enviro EF3 Pellet Stoves and Inserts



FEATURES	EF 3Bi FS	EF 3 Bi FPI
Nickel Door cover	O	O
24kt Gold Door cover	O	O
Large full pedestal ash pan	S	-
Power usage (ignitor on)	520W	520W
Power usage (ignitor off)	250W	250W
Hopper lid handle	S	S
Heat exchanger	S	S
Fire box brick lining	S	S
160 cfm convection fan (variable speed)	S	S
Concealed electronic control panel	S	S
Ignitor	S	S
Oversized surround	-	O
EF log set	O	O
Zero clearance kit	-	O
Concealed Door Handle	S	S
Mobile Home Approved***	S	S


  

SPECIFICATIONS	EF 3Bi FS	EF 3 Bi FPI
Fuel Capacity	55lbs	55lbs
Weight of complete unit	240lbs	240lbs
Efficiency Rating	75.8%	75.8%
Btu(kW) input (on high)	40,000 (11.7)	40,000 (11.7)
Btu(kW) input (on low)*	6,500 (1.9)	6,500 (1.9)
Area heated**	1,000-1,800ft <sup>2</sup>	1,000-1,800ft <sup>2</sup>


  

DIMENSIONS AT BACK OF UNIT	FS	FPI
Width X Depth	22" X 24"	22" X 24"
Height	30.5"	22.75"
A. Front of unit on hearth	-	13"
B. Recess depth into fireplace	-	11"
Standard Surround (H X W)	-	30" X 40"
Oversized Surround (H X W)	-	33" X 46"
C. Side wall to unit	6"	8"
D. Back wall to unit	1"	-
E. Wall to corner of unit	1"	-
F. Floor protector (in front of unit)††	6"	6"
G. Top of unit to mantle	-	8"
H. Unit top to surround top	-	8"
I. Unit to mantle pillar	-	6"


S = STANDARD EQUIPMENT  
O = OPTIONAL EQUIPMENT




Front View - Insert




Side View - Insert



Front View - Free-Standing



Top View - Free-Standing



Recommended Framing Dimensions  
Zero Clearance Units

ALCOVE INSTALLATION  
Model FS may be installed in an alcove at least 36" wide x 48" high x 30" deep.

These classic heating products from Enviro have beautifully clean lines. They are built to the same high standards of quality and performance that you have come to expect from all Enviro models. Easy-to-use controls, large hoppers and ash pans make these pellet stoves simple to operate. Form and function are blended together to create a truly marvelous heater.



Listed By **O-T-L** Portland Oregon USA  
OMNI-Test Laboratories, Inc.



Please share and recycle this brochure

Enviro Pellet Stoves have been tested and listed by Intertek Testing Ltd to Standards:  
Approved for Sale in Europe UL-1482/ULC S627, CSAB366.2M/ULC S628 UL907/UL-127 ULC S610

\* Figures will vary considerably with individual conditions and fuel quality.  
\*\* Figures will vary considerably with floor plan, house layout and heat loss of the house.

\*\*\* Enviro pellet appliances are approved for mobile home installations once certain criteria are met.  
†† Floor protector must be the full width and depth of the unit plus extend 6" in front of the unit.  
Specifications are subject to change without notice. These units must be installed by a qualified dealer.



AUTHORIZED DEALER